

BASEBOARD BA 700


PRODUCT DESCRIPTION



The BA700 is a PVC baseboard profile that can be attached using adhesive or metal fasteners. The profile has a small fitting on the upper part to facilitate adhesive and avoid the accumulation of dust and dirt on the edge.

TECHNICAL FEATURES

Length: 6' 6" 3/4 - 2.00 meters



Expanded PVC

H1 = 5/16" - 8 mm

H = 11/16" - 17.5 mm

MATERIAL DESCRIPTION

PVC

RESINTOP Rigid thermoplastic synthetic resin:

This material is specifically formulated to optimize the performance of rigid profiles intended for permanent indoor and outdoor applications, where both aesthetic and durability requirements must be met. Produced from primary resin with a Polyvinyl Chloride (PVC)-based composition, it is suitable for a wide range of uses at temperatures up to +60°C. The selected raw material ensures excellent resistance to UV rays, limited mechanical impacts, and strong protection against the stagnation of fungi and bacteria.



P12



P22



P51



P79

baseboard >> BA700 in Expanded PVC		
Item	B inch	Finish
BA700P12200	2-3/4	P12 - Ivory White
BA700P22200	2-3/4	P22 - Pastel Grey
BA700P51200	2-3/4	P51 - Black
BA700P79200	2-3/4	P79 - Walnut

APPLICATION

1. Check that the substrate is solid, flat, clean, degreased and dry, verifying that the application temperature is not lower than 15°C in case of gluing;
2. Cut the profile to the required length;
3. Apply the adhesive (FIXXTEC) to the part of the profile to be adhesived, or remove the protective paper from the adhesive for self-adhesive versions, and position the profile correctly without further adjustments;
4. Apply the profile with uniform pressure without hammering;
5. Remove any adhesive residue from the profile immediately.

CLEANING AND MAINTENANCE

SYNTHETIC RESIN:

Das thermoplastische Kunstharz erfordert keine besondere Wartung.

Es lässt sich leicht mit farblosem, in Wasser verdünntem Alkohol oder mit normalen, ebenfalls in Wasser verdünnten Reinigungsmitteln reinigen, sofern diese nicht säurehaltig sind. Spülen Sie es zum Schluss nur mit Wasser ab. Verwenden Sie nicht scheuernde Schwämme oder Tücher, um Kratzer auf der Oberfläche zu vermeiden.

WARNINGS

The indications and specifications contained herein, while consistent with our experience, are intended to be purely indicative and require confirmation through extensive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm, as a floor closing
 profile and protection of the perimeter expansion joint.

Family type _____ of the Profilitec company as a skirting board profile to be supplied and installed
 properly, following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com