

## BASEBOARD BFZ


### PRODUCT DESCRIPTION



BFZ is a construction profile that allows you to create a flush-to-the-wall baseboard with the same material as the flooring. In the lower part there are special grooves, designed to allow the insertion of a linear profile which will help to determine the level of the screed and ensure perfect positioning of the heights of doors and windows.

### TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Aluminum

### MATERIAL DESCRIPTION

#### Aluminum

The primary aluminum alloy EN AW-6060 in T6 temper is suitable for complex extrusions, offering high strength and an excellent natural surface finish that lends itself well to subsequent finishing processes.



AN

plano >> BFZ in Aluminum for construction		
Item	HxB inch	Finish
BFZ1000/130AN270	1/2x4-3/4	AN - Natural

## APPLICATION

1. Cut the profile to the required length;
2. Fix the profile to the wall using mortar or plugs with countersunk screws;
3. Assemble the profile before embedding the various pipes/cables in the screed;
4. On the lower part there are special grooves, designed to allow the insertion of a flat linear profile supplied in the package, created to determine the level of the screed and guarantee perfect positioning of the heights of doors and windows;
5. Pour the screed and lay the floor respecting the drying times of the cementitious products and thicknesses used;
6. Once the floor has been laid, make a 6 cm skirting board of the same material as the floor.

## CLEANING AND MAINTENANCE

### ALUMINIUM:

Aluminum requires no special maintenance.

For cleaning, use colorless alcohol diluted in water or neutral detergents, avoiding acidic ones (e.g., hydrochloric or hydrofluoric acid); use non-abrasive sponges or cloths to avoid damage. We recommend not applying cleaners directly to surfaces. After cleaning, rinse with water and dry immediately with a soft cloth. Avoid polishes. Quickly remove residual cement or grout to protect the surface.

## WARNINGS

These profiles must be handled with care, taking care to use cut-resistant gloves. The instructions and requirements contained herein, while based on our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for use and assumes all responsibility for any damage resulting from incorrect installation of the material.

## BILL OF QUANTITIES ITEM

Supply and installation of profile in \_\_\_\_\_ (material), with finish \_\_\_\_\_  
 \_\_\_\_\_ (see Material Description section) of characteristic size \_\_\_\_\_ mm, as profile  
 Used as a reference point for installing doors and windows. Designed to create a 2-3/8" - 6 cm skirting board of the same material as the floor.

Family type \_\_\_\_\_ from the Profilitec company as a skirting board support profile made of the same material as the floor, to be applied to the wall before pouring the screed and installing the floor. Profile to be supplied and installed according to the rules and fields of application indicated by the manufacturer.

Profile length: 2700 mm

Profile SKU: \_\_\_\_\_

Material: \_\_\_\_\_ \$/pc

Installation: \_\_\_\_\_ \$/pc

Totale price: \_\_\_\_\_ \$/pc

**Profilitec S.p.A.**  
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY  
 Tel: +39 0444 268311  
 e-mail: profilitec@profilitec.com

**Profilitec Corp.**  
 e-mail: customerservice@profilitec.com

**Profilitec Ibérica, S.L.U.**  
 e-mail: iberica@profilitec.com

**Profilitec France**  
 e-mail: france@profilitec.com