

COFLEX CD


PRODUCT DESCRIPTION



COFLEX CD mortar bed movement joints in co-extruded synthetic resin are conceived to subdivide large tile bays. Extension clips may be vertically interlocked to match high thicker mortar beds. Exclusively suitable for pedestrian traffic, this profile provides limited protection to the tile edges and compensates slight differential movement due to substrate contraction and expansion. They are installed with thin-set mortar. Ideally used in retail shops, hotels, sports facilities and schools. Suggested floor bays: 172-7/32"ft2 (16m2).

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Coextruded Synthetic Resinil + Resinflex

B = 5/16" - 8 mm

MATERIAL DESCRIPTION

Coextruded Synthetic Resinil + Resinflex

RESINIL Thermoplastic synthetic resin for COEXTRUSION:

Made from primary resin whose composition based on Polyvinyl Chloride characterizes it for high resistance and optimized compatibility with regards to long-lasting adhesion with plasticized resins used in the coextrusion process, i.e. the permanent union of two materials with different degrees of Shore hardness.

RESINFLEX Plasticized thermoplastic synthetic resin:

Made from primary resin, its polyvinyl chloride composition provides high resistance and compatibility with Resinil in the COEXTRUSION process we use in most expansion joints. Thanks to the nature of the plasticizers used, the material maintains its essential elasticity characteristics over time.



P23



P10

coflex >> CD in PVC		
Item	H inch	Finish
CD230P10270	29/32	P10 - Grey + Trasparent
CD230P23270	29/32	P23 - Cement Grey
CD220P270	29/32	P23 - Extension



APPLICATION

1. Cut the profile to the required length;
2. Make sure that the groove or gap to be filled is the right size for the profile to fit into.
3. In general, for wooden floors calculate 1/64" - 0.5 mm less than the joint, for stone and ceramic floors the measurement is that of the joint;
4. Apply the adhesive (FIXXTEC) in the groove;
5. Position the profile by inserting it with uniform pressure and using a rubber mallet;
6. Remove any glue residue from the profile immediately;
7. Assemble the subsequent elements until the desired height is reached.

CLEANING AND MAINTENANCE

SYNTHETIC RESIN:

Das thermoplastische Kunstharz erfordert keine besondere Wartung.

Es lässt sich leicht mit farblosem, in Wasser verdünntem Alkohol oder mit normalen, ebenfalls in Wasser verdünnten Reinigungsmitteln reinigen, sofern diese nicht säurehaltig sind. Spülen Sie es zum Schluss nur mit Wasser ab. Verwenden Sie nicht scheuernde Schwämme oder Tücher, um Kratzer auf der Oberfläche zu vermeiden.

WARNINGS

The indications and specifications contained herein, while consistent with our experience, are purely indicative and require confirmation through extensive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm, equipped with a conical lateral surface with undercut teeth that guarantee a perfect grip when cutting the screed and with an elastic internal part for better control of expansions in compression.

Family type _____ from the Profilitec company as an elastic modular distribution joint and covering protection joint to be supplied and installed according to the rules of the art, respecting the methods and fields of application indicated by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com