

COFLEX CMB


PRODUCT DESCRIPTION



Joint recommended for mortar laying, manufactured from double-density synthetic material. It is composed of two rigid structural parts joined by soft plastic coated material inserts, available in multiple colors. The CMB joint is used to split the subfloor or screed as required by the project.

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



CMB P23

B = 5/16" - 8 mm

B1 = 3-9/64" - 80 mm

MATERIAL DESCRIPTION

Coextruded Synthetic Resinil + Resinflex

RESINIL Thermoplastic synthetic resin for COEXTRUSION:

Made from primary resin whose composition based on Polyvinyl Chloride characterizes it for high resistance and optimized compatibility with regards to long-lasting adhesion with plasticized resins used in the coextrusion process, i.e. the permanent union of two materials with different degrees of Shore hardness.

RESINFLEX Plasticized thermoplastic synthetic resin:

Made from primary resin, its polyvinyl chloride composition provides high resistance and compatibility with Resinil in the COEXTRUSION process we use in most expansion joints. Thanks to the nature of the plasticizers used, the material maintains its essential elasticity characteristics over time.



P23

coflex >> CMB Co-extruded Synthetic Resinil + Resinflex		
Item	H1 inch	Finish
CMB300P23270	1-3/16	P23 - Cement Grey
CMB450P23270	1-25/32	P23 - Cement Grey
CMB600P23270	2-3/8	P23 - Cement Grey



APPLICATION

1. Choose the profile according to the loads and expansion to which it will be subjected. If necessary, level the subfloor using a layer of plastic mortar with a width of 3-15/16" - 10 cm approx. Calculating in advance that when the laying is completed the joint will be perfectly flush with the finished floor;
2. Spread the adhesive in the profile application area with the help of a notched trowel;
3. Cut the profile to the required length;
4. Align the joint, checking that it is perfectly linear. If present, fix the wings to the substrate using mechanical or chemical expansion plugs sized according to the loads and characteristics of the substrate;
5. Fixing must be carried out in parallel on both sides of the profile, positioning, if required, a plug every 30 cm, using the external holes alternately between the two fixing wings;
6. If necessary, depending on the type of wall covering material, a 1/8" - 3 mm to 3/16" - 5 mm elastic seal between the final edge of the wall covering and the profile is recommended.

CLEANING AND MAINTENANCE

SYNTHETIC RESIN:

Das thermoplastische Kunstharz erfordert keine besondere Wartung.

Es lässt sich leicht mit farblosem, in Wasser verdünntem Alkohol oder mit normalen, ebenfalls in Wasser verdünnten Reinigungsmitteln reinigen, sofern diese nicht säurehaltig sind. Spülen Sie es zum Schluss nur mit Wasser ab. Verwenden Sie nicht scheuernde Schwämme oder Tücher, um Kratzer auf der Oberfläche zu vermeiden.

WARNINGS

The indications and specifications contained herein, while consistent with our experience, are purely indicative and require confirmation through extensive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm, equipped with a support base with ribs that guarantees a perfect grip with the adhesive used and with an internal part made up of elastic elements for better control of expansions in compression.

Family type _____ from the Profilitec company as an elastic joint for mortar installation and for protecting the covering suitable for medium loads and vehicles to be supplied and installed according to the rules of the art, respecting the methods and fields of application indicated by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com
Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com