

COFLEX CT


PRODUCT DESCRIPTION



This is an expansion joint with a metal structure and an infill suitable for sanding and grinding. Ideal for porcelain tile. The robust, continuous metal angles of the profile protect tile edges, marble or stone and reduce mechanical stresses which can compromise the integrity of the flooring when exposed to intense passage. The metal parts on the sides of the joint are composed of Trimtec profiles with a rounded top edge and perforation designed to absorb elevated loads and tension which impact the flooring and become a single element with the tile and thin-set mortar. The hardness of the EPDM infill is a perfect compromise between flexibility and resistance. Typical flooring areas: retail shops, hotels, sporting centers and schools.

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Stainless Steel + EPDM polishable insert

B = 7/16" - 11 mm

H1 = 19/32" - 15 mm

MATERIAL DESCRIPTION

Stainless Steel + EPDM polishable insert

Steel profiles are made by cold forming sheets of constant thickness, thus differing from the corresponding aluminum and brass versions made by hot extrusion, while maintaining their application and dimensional characteristics. Stainless steel effectively resists high mechanical stress and is particularly suitable for use in the chemical, food, and hospital sectors, where hygiene, durability, and chemical resistance are essential. Normally produced with a semi-gloss finish, a brushed finish can also be achieved by partially removing material using rotating nylon and quartz fiber brushes. This process gives the surface a matte appearance without altering its characteristics.

AISI 304 STAINLESS STEEL - EN X 5 CrNi 18 10 - DIN 1.4301:

This steel belongs to the AUSTENITIC category and is the most widespread and commonly used alloy for products requiring high technical and performance characteristics. It is highly resistant to most chemical agents but may stain or darken superficially; a standard polishing product is sufficient to restore its original appearance.

RESINPRENE Vulcanized rubber:

Resinprene vulcanized rubber is a modified EPDM-based compound whose particular characteristics we highlight:

Optimal mechanical properties in an operating temperature range from -40°C to $+150^{\circ}\text{C}$

Resistance to aqueous fluids, oils, and hydrocarbons. Low permanent deformation in compression and tension. Excellent resistance to aging. Exceptional resistance to dynamic fatigue and tearing. The intrinsic characteristics of the material make it particularly suitable for the production of profiles requiring high performance over time, both indoors and outdoors.



IL



P23



P51

coflex >> CT in Stainless Steel AISI 304 - DIN. 1.4301 - Polished + Insert EPDM

Item	H inch	Finish
CT80IL23270	5/16	IL23 - Cement Grey
CT100IL23270	3/8	IL23 - Cement Grey
CT125IL23270	1/2	IL23 - Cement Grey
CT150IL23270	9/16	IL23 - Cement Grey
CT200IL23270	3/4	IL23 - Cement Grey
CT80IL51270	5/16	IL51 - Black
CT100IL51270	3/8	IL51 - Black
CT125IL51270	1/2	IL51 - Black
CT150IL51270	9/16	IL51 - Black
CT200IL51270	3/4	IL51 - Black



APPLICATION

1. Choose the H-size profile corresponding to the thickness of the tile to be laid, taking care to ensure that the profile does not exceed the edge of the floor but is positioned 0.5 to 1 mm lower.
2. Spread the adhesive in the profile application area with the help of a notched trowel;
3. Cut the profile to the required length and place it so that the base sinks into the adhesive, pressing and aligning it;
4. Apply an additional layer of adhesive to the perforation and in the cavities of the vertical section of the profile in contact with the edge of the floor;
5. Generally leave a space of about 3/32" - 2 mm between the profile and the edge of the tile to be filled later with sealant or grout;
6. Remove any adhesive residue from the profile immediately.

CLEANING AND MAINTENANCE

STAINLESS STEEL:

Stainless steel is easy to clean and very hygienic because of its smooth, nonporous surface, which hinders the growth of bacteria. To keep it in good condition, simply wash it with warm soapy water, rinse it thoroughly and dry it with a soft cloth. If exposed to weathering, periodic cleaning is recommended to prevent corrosion. Brushed surfaces should be cleaned in the direction of brushing. In case of scratches, a specific polish can be used with a soft cloth.

Avoid cleaning agents containing hydrochloric acid, hydrofluoric acid or bleach, as well as abrasive products. Do not leave ordinary steel objects in contact with stainless steel to prevent contamination and rust stains. Also, do not leave damp patches or sponges on the surface to prevent water halos.

WARNINGS

These profiles should be handled with care, using cut-resistant gloves. The indications and prescriptions herein, while corresponding to our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines any responsibility for any damage to people or things resulting from improper use of the products. The user is required to determine whether or not the product is suitable for use and assumes all responsibility arising from incorrect installation of the material.

Profilitec S.p.A.
Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
Tel: +39 0444 268311
e-mail: profilitec@profilitec.com

Profilitec Corp.
e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
e-mail: iberica@profilitec.com

Profilitec France
e-mail: france@profilitec.com

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm, equipped with a
 perforated fin which guarantees perfect positioning under the tile used and with an internal part closed by an elastic
 element in vulcanised EPDM rubber for better control of expansions in compression and durability over time.

Family type _____ of the Profilitec company as an elastic joint and protection of the covering to be
 supplied and installed properly following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc