

LEVELTEC ZP


PRODUCT DESCRIPTION



A selection of full brass extruded profile shapes for existing floor edges and/or junctions with a 3/8" (10mm) drop level to connect to flooring materials or fit onto pre-laid floors. It is highly suitable for rapidly connecting differing floors such as ceramic to wood or other combinations and wherever a jointing profile has not been planned during the laying job.

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Brass

B = 1-1/16" - 27 mm

MATERIAL DESCRIPTION

Brass

Profiles made from CW618N (EN 12167) brass alloy are characterized by high resistance to mechanical stress, making them particularly suitable for heavy-traffic applications, such as industrial settings and at expansion joints.

Brass is resistant to most chemical agents commonly encountered during the installation of ceramic coverings. However, in the presence of humidity or aggressive substances, the surface may develop superficial oxidation, which can be removed using a standard polishing product.

These profiles can be manufactured through either hot extrusion or cold forming from sheets of constant thickness.

POLISHED BRASS:

This finish is obtained using specialized polishing machines that mechanically enhance the surface without altering the material's intrinsic properties. In the presence of oxidizing agents, some surface darkening may occur, which can be easily restored using common polishing products.



OL

leveltec >> ZP in Polished Brass		
Item	H inch	Finish
ZP1000L270	3/8	OL - Polished

APPLICATION

1. Using a spatula, spread the adhesive such as FIXXTEC in the application area corresponding to the base and the support back of the profile;
2. Cut the profile to the required length and place it with the perforated side in the adhesive, pressing it and aligning it with the floor;
3. Generally, leave a gap of about 3/32" - 2 mm between the profile and the edge of the tile to be filled later with sealant or filler; in the case of wood, the gap may be minimal.

CLEANING AND MAINTENANCE

BRASS:

Brass does not require special maintenance and is easily cleaned with alcohol diluted in water or with neutral detergents, avoiding those with an acidic base.

It is recommended to use water with mild detergents, ensuring the final rinse is with water only. To avoid scratches, use exclusively non-abrasive cloths or sponges. For maintenance, common polishes available on the market can be used.

WARNINGS

These profiles should be handled with care, using cut-resistant gloves. The indications and prescriptions herein, while corresponding to our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines any responsibility for any damage to people or things resulting from improper use of the products. The user is required to determine whether or not the product is suitable for use and assumes all responsibility arising from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm. Profile with dovetail internal part for better adhesive adhesion.

Family type _____ from the Profilitec company as a finishing and connection profile between existing floors and new flooring to be supplied and installed properly, following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com