

LINETEC PR


PRODUCT DESCRIPTION



A selection of full brass extruded profile shapes for existing floor edges and/or junctions with a 3/8" (10mm) drop level to connect to flooring materials or fit onto pre-laid floors. It is highly suitable for rapidly connecting differing floors such as ceramic to wood or other combinations and wherever adjoining profile has not been planned during the laying job.

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Brass

MATERIAL DESCRIPTION

Brass

Profiles made from CW618N (EN 12167) brass alloy are characterized by high resistance to mechanical stress, making them particularly suitable for heavy-traffic applications, such as industrial settings and at expansion joints. Brass is resistant to most chemical agents commonly encountered during the installation of ceramic coverings. However, in the presence of humidity or aggressive substances, the surface may develop superficial oxidation, which can be removed using a standard polishing product.

These profiles can be manufactured through either hot extrusion or cold forming from sheets of constant thickness.

POLISHED BRASS:

This finish is obtained using specialized polishing machines that mechanically enhance the surface without altering the material's intrinsic properties. In the presence of oxidizing agents, some surface darkening may occur, which can be easily restored using common polishing products.



OL

linetec >> PR in Polished Brass		
Item	HxB inch	Finish
PR100L270	3/8x3/8	OL - Polished

APPLICATION

1. Choose the PR profile in the desired material and finish;
2. Cut to the desired length;
3. Thoroughly clean the surfaces that will be covered by the profile after installation;
4. Fill the joint space with FIXXTEC or with the adhesive used for laying the floor;
5. Sink the profile into the adhesive, making sure that the profile is level with the coverings to be joined;
6. Apply and maintain uniform pressure for a few minutes along the entire profile to optimize adhesion to the installation surface.

CLEANING AND MAINTENANCE

BRASS:

Brass does not require special maintenance and is easily cleaned with alcohol diluted in water or with neutral detergents, avoiding those with an acidic base.

It is recommended to use water with mild detergents, ensuring the final rinse is with water only. To avoid scratches, use exclusively non-abrasive cloths or sponges. For maintenance, common polishes available on the market can be used.

WARNINGS

These profiles should be handled with care, using cut-resistant gloves. The indications and prescriptions herein, while corresponding to our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines any responsibility for any damage to people or things resulting from improper use of the products. The user is required to determine whether or not the product is suitable for use and assumes all responsibility arising from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm. Profile with
 connected upper part for an ideal floor finish.

Family type _____ from the Profilitec company as a finishing profile connecting existing floors and
 new flooring to be supplied and installed properly, following the methods and fields of application suggested by the
 manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com