

PLANO PS130


PRODUCT DESCRIPTION



Drywall is the most commonly used material in modern residential and commercial construction. PLANO PS130, a new, one-of-a-kind profile elegantly finishes drywall ceiling and wall installations. Its discreet, 33/64"x33/64" (13x13mm) profile section perfectly edges drywall panels, becoming a minimalist design feature. At the floor level, the profile connects with the PLANO DESIGN BF baseboard for a fully integrated installation. The result is a profile that leaves a small gap of negative space, almost suspending the wall in mid-air.

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Aluminum

B = 33/64" - 13 mm

H1 = 15/16" - 23.8 mm

MATERIAL DESCRIPTION

Aluminum

The primary aluminum alloy EN AW-6060 in T6 temper is suitable for complex extrusions, offering high strength and an excellent natural surface finish that lends itself well to subsequent finishing processes.

-

ANODIZED ALUMINUM:

The anodic oxidation process provides protection against corrosion caused by atmospheric agents, without involving galvanic treatments.

In accordance with the EN 12373 standard, profiles undergo preliminary treatments that create a uniformly matte surface. They are then colored through an electrochemical oxidation process in standard finishes: Silver, Gold, Bronze, Copper, and Titanium, with a coating thickness of up to 20 microns.

POWDER COATED ALUMINUM:

Powder coating begins with a chromium phosphate pre-treatment, followed by electrostatic application of polyester powders that offer high resistance to U.V. rays and atmospheric agents. The entire surface of the profile is coated with an average thickness of approximately 60 microns. A hot cross-linking polymerization process is then carried out to ensure maximum chemical and mechanical resistance.



AS



AGR



AM11



A54

plano >> PS130 Anodized Aluminum Drywall Profile		
Item	H inch	Finish
PS130AS270	33/64	AS - Silver
PS130AGR270	33/64	AGR - Graphite

plano >> PS130 Powder Coated Aluminum Drywall Profile		
Item	H inch	Finish
PS130AM11270	33/64	AM11 - Matt white
PS130A54270	33/64	A54 - Matt Black

APPLICATION

1. Cut the skirting board to the desired length;
2. Clean the supporting wall from oil, grease and general dirt residues;
3. Apply FIXXTEC multipurpose sealant to the upper and lower parts of the profile;
4. Press the profile against the wall or ceiling using adequate pressure;
5. Then install the plasterboard wall by placing the sheets on the horizontal support panel and fixing them with screws;
6. If the surface is uneven or difficult to clean, or if there is no wall and only a supporting frame, secure the skirting board with screws, securing it from the top, which will be covered by the plasterboard.

CLEANING AND MAINTENANCE

ALUMINIUM:

Aluminum requires no special maintenance.

For cleaning, use colorless alcohol diluted in water or neutral detergents, avoiding acidic ones (e.g., hydrochloric or hydrofluoric acid); use non-abrasive sponges or cloths to avoid damage. We recommend not applying cleaners directly to surfaces. After cleaning, rinse with water and dry immediately with a soft cloth. Avoid polishes. Quickly remove residual cement or grout to protect the surface.

WARNINGS

These profiles should be handled with care, using cut-resistant gloves. The indications and prescriptions herein, while corresponding to our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines any responsibility for any damage to people or things resulting from improper use of the products. The user is required to determine whether or not the product is suitable for use and assumes all responsibility arising from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm, as a profile equipped with a horizontal section to support the sheet for assembly and a rear fin for fixing to the wall using screws with a skirting or decorative function.

Family type _____ from the Profilitec company as a floor closing and wall finishing profile with plasterboard panels, to be supplied and installed properly, following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com