

## SANITEC ER


### PRODUCT DESCRIPTION



SANITEC ER Internal corner cove-shaped profiles are easy to clean and designed to meet hygiene standards in public spaces subject to sanitary inspection, such as hospitals, food processing plants and industrial kitchens. Installed on site prior to the wall and floor coverings, the profile perfectly integrates into the corner detail.

### TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Synthetic Colormassa Resinil

R = 5/8" - 16 mm

H1 = 19/32" - 15 mm

### MATERIAL DESCRIPTION

#### Synthetic Colormassa Resinil

RESINTOP Rigid thermoplastic synthetic resin:

This material is specifically formulated to optimize the performance of rigid profiles intended for permanent indoor and outdoor applications, where both aesthetic and durability requirements must be met. Produced from primary resin with a Polyvinyl Chloride (PVC)-based composition, it is suitable for a wide range of uses at temperatures up to +60°C. The selected raw material ensures excellent resistance to UV rays, limited mechanical impacts, and strong protection against the stagnation of fungi and bacteria.



P11



P22

sanitec >> ER Synthetic Resin Full Body Colored Resinil		
Item	H inch	Finish
ER9P11270	11/32	P11 - Pure White
ER11P11270	7/16	P11 - Pure White
ER9P22270	11/32	P22 - Pastel Grey
ER11P22270	7/16	P22 - Pastel Grey

sanitec >> ERI Internal Corner Junction synthetic resin		
Item	H inch	Finish
ERIP11SET	X	P11 - Pure White
ERIP22SET	X	P22 - Pastel Grey

sanitec >> ERE External Corner Junction in Synthetic Resin		
Item	H inch	Finish
EREP11SET	X	P11 - Pure White
EREP22SET	X	P22 - Pastel Grey

sanitec >> ERF End cap in Synthetic Resin		
Item	H inch	Finish
ERFP11SET	X	P11 - Pure White
ERFP22SET	X	P22 - Pastel Grey

sanitec >> ERT Three-way Junction in Synthetic Resin		
Item	H inch	Finish
ERTP11SET	X	P11 - Pure White
ERTP22SET	X	P22 - Pastel Grey

## APPLICATION

1. Choose a profile according to tile thickness and desired finish;
2. Cut to the desired length;
3. Spread the adhesive in the profile application area with the help of a notched trowel;
4. Position the profile by pressing it so that it is embedded in it, and then spread the resulting excess adhesive on the surface of the flap;
5. Lay the tiles, taking care to align them with the profile and leave a gap of about 3/32" - 2 mm. The profile laid properly should be installed in the same plane as the tile;
6. To apply special pieces such as external and internal corners, joints, and end caps, use a specific, long-lasting flexible adhesive such as FIXXTEC. Before application, make sure the joint surface is free of grease or similar substances, which could compromise proper bonding;
7. Clean any glue residue from the profile before it dries. Thoroughly seal joints between profile and tile.

## CLEANING AND MAINTENANCE

### SYNTHETIC RESIN:

Das thermoplastische Kunstharz erfordert keine besondere Wartung.

Es lässt sich leicht mit farblosem, in Wasser verdünntem Alkohol oder mit normalen, ebenfalls in Wasser verdünnten Reinigungsmitteln reinigen, sofern diese nicht säurehaltig sind. Spülen Sie es zum Schluss nur mit Wasser ab. Verwenden Sie nicht scheuernde Schwämme oder Tücher, um Kratzer auf der Oberfläche zu vermeiden.

## WARNINGS

These profiles should be handled with care, using cut-resistant gloves. The indications and prescriptions herein, while corresponding to our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines any responsibility for any damage to people or things resulting from improper use of the products. The user is required to determine whether or not the product is suitable for use and assumes all responsibility arising from incorrect installation of the material.

**Profilitec S.p.A.**  
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY  
 Tel: +39 0444 268311  
 e-mail: [profilitec@profilitec.com](mailto:profilitec@profilitec.com)

**Profilitec Corp.**  
 e-mail: [customerservice@profilitec.com](mailto:customerservice@profilitec.com)

**Profilitec Ibérica, S.L.U.**  
 e-mail: [iberica@profilitec.com](mailto:iberica@profilitec.com)

**Profilitec France**  
 e-mail: [france@profilitec.com](mailto:france@profilitec.com)

## BILL OF QUANTITIES ITEM

Supply and installation of profile in \_\_\_\_\_ (material), with finish \_\_\_\_\_  
 \_\_\_\_\_ (see Material Description section) of characteristic size \_\_\_\_\_ mm, with concave  
 sanitary cove function and a curvature radius of 5/8" - 16 mm.

Profile family type \_\_\_\_\_ of Profilitec company as a closing and protection profile for the covering,  
 to be supplied and installed in a professional manner, respecting the methods and application fields indicated by the  
 manufacturer.

Profile length: 2700 mm

Profile SKU: \_\_\_\_\_

Material: \_\_\_\_\_ \$/pc

Installation: \_\_\_\_\_ \$/pc

Totale price: \_\_\_\_\_ \$/pc

**Profilitec S.p.A.**  
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY  
 Tel: +39 0444 268311  
 e-mail: [profilitec@profilitec.com](mailto:profilitec@profilitec.com)

**Profilitec Corp.**  
 e-mail: [customerservice@profilitec.com](mailto:customerservice@profilitec.com)

**Profilitec Ibérica, S.L.U.**  
 e-mail: [iberica@profilitec.com](mailto:iberica@profilitec.com)

**Profilitec France**  
 e-mail: [france@profilitec.com](mailto:france@profilitec.com)