

SANITEC SB24


PRODUCT DESCRIPTION



Hygienic cove shaped profile between wall and wall and between wall and floor. Connections between the wall and the bathtub, the shower tray or the kitchen surface. The silicones that are normally used lose their anti-mold properties after few months producing unsightly halos or stains. SB24 is easily applied with FIXXTEC on coverings, improves or restores the appearance of corners, making them more hygienic.

TECHNICAL FEATURES

Length: 2.70 meters - 8'10"



Synthetic Resin

MATERIAL DESCRIPTION

Synthetic Resin Colormassa Resinil + Resinflex

RESINIL Thermoplastic synthetic resin for COEXTRUSION:

Made from primary resin whose composition based on Polyvinyl Chloride characterizes it for high resistance and optimized compatibility with regards to long-lasting adhesion with plasticized resins used in the coextrusion process, i.e. the permanent union of two materials with different degrees of Shore hardness.

RESINFLEX Plasticized thermoplastic synthetic resin:

Made from primary resin, its polyvinyl chloride composition provides high resistance and compatibility with Resinil in the COEXTRUSION process we use in most expansion joints. Thanks to the nature of the plasticizers used, the material maintains its essential elasticity characteristics over time.



P11

sanitec >> SB 24 in Synthetic Resin Full Body Colored Resinil + Resinflex		
Item	B inch	Finish
SB24P11270	1	P11 - Pure White + Trasp. lips

APPLICATION

1. Cut the profile to the required length;
2. Apply the adhesive (FIXXTEC) to the part of the profile to be adhesived, or remove the protective paper from the adhesive for self-adhesive versions, and position the profile correctly without further adjustments;
3. Apply the profile with uniform pressure without hammering;
4. Remove any adhesive residue from the profile immediately.

CLEANING AND MAINTENANCE

SYNTHETIC RESIN:

Das thermoplastische Kunstharz erfordert keine besondere Wartung.

Es lässt sich leicht mit farblosem, in Wasser verdünntem Alkohol oder mit normalen, ebenfalls in Wasser verdünnten Reinigungsmitteln reinigen, sofern diese nicht säurehaltig sind. Spülen Sie es zum Schluss nur mit Wasser ab. Verwenden Sie nicht scheuernde Schwämme oder Tücher, um Kratzer auf der Oberfläche zu vermeiden.

WARNINGS

The indications and specifications contained herein, while consistent with our experience, are purely indicative and require confirmation through extensive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
 _____ (see Material Description section) of characteristic size _____ mm, with connecting
 curve and transparent edges.

Family type _____ from the Profilitec company as a concave sanitary cove to be applied as a
 connection between the wall and the bathtub or shower, to be supplied and installed properly, following the methods and
 fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Totale price: _____ \$/pc

Profilitec S.p.A.
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
 Tel: +39 0444 268311
 e-mail: profilitec@profilitec.com

Profilitec Corp.
 e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
 e-mail: iberica@profilitec.com

Profilitec France
 e-mail: france@profilitec.com