



WALKTEC SWH

PRODUCT DESCRIPTION



Durable and safe carborundum mineral grain strips are a reliable tool for slip-resistance. WALKTEC ready-to-use adhesive strips can be applied to any surface. To enhance safety measures, we recommend applying double strips.

TECHNICAL FEATURES



SWH

MATERIAL DESCRIPTION

Adhesive carborundum

Non-slip material

walktec >> SWH Carborundum self-adhesive "Strip Walk"		
Item	BxL inch	Finish
SWH25C10	1x60'	C10 - Transparent
SWH25C11	1x60'	C11 - White
SWH25C51	1x60'	C51 - Black
SWH19C51	3/4x60'	C51 - Black
SWH50C51	2x60'	C51 - Black
SWH19CF	3/4x60'	CF - Photoluminescent

walktec >> SWHS Carborundum self-adhesive "Strip Walk"		
Item	BxL inch	Finish
SWHS19C51	3/4x2'1/2"	C51 - Black

APPLICATION

1. Clean and degrease the surface on which to apply the product.
2. The surface of the substrate must be smooth.
3. For substrates with poor adhesion, use an adhesion promoting primer.
4. Apply the non-slip adhesive strip, avoiding overlaps and bubbles.

WARNINGS

Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of non-slip Carborundum strips, with _____ finish (see Material Description section) of characteristic size _____ mm. Strips with non-slip surface. Family type _____ of the Profilitec company as safety and accident prevention strips to be supplied and installed according to the rules of the art, respecting the methods and fields of application indicated by the manufacturer.

Product Code: _____

Material: _____ \$/pc

Installation: _____ \$/pc

Total price: _____ €/m"