

## BASEBOARD BAR


### PRODUCT DESCRIPTION



Decorative baseboard with multi-line ribbed effect in the visible part which matches the decorative standard of kitchen furniture. Available either with or without self-adhered backing. Long lasting and elegant finish. The profile contoured ends give a snug fit on the wall covering over the bottom perimeter.

### TECHNICAL FEATURES

Length: 2,70 meters



Aluminum

H1 = 10 mm

### MATERIAL DESCRIPTION

#### Aluminum

The primary aluminum alloy EN AW-6060 in T6 temper is suitable for complex extrusions, offering high strength and an excellent natural surface finish that lends itself well to subsequent finishing processes.

#### ANODIZED ALUMINUM:

The anodic oxidation process provides protection against corrosion caused by atmospheric agents, without involving galvanic treatments.

According to the EN 12373 standard, the profiles are treated with preventive processes that make them uniformly opaque, subsequently they are coloured through an electro-chemical oxidation process in the standard colours Silver, Gold, Bronze, Copper and Titanium with a thickness of up to 10 microns.



AS

## ACCESSORIES



BAE-P



BAI-P



BAT-P

<b>baseboard &gt;&gt; BAR Multiline in Anodized Aluminum - Self-Adhesive</b>		
<b>Item</b>	<b>B mm</b>	<b>Finish</b>
BAR600ASA270	60	AS - Silver

<b>baseboard &gt;&gt; BAR Multiline in Anodized Aluminum - not Adhesive</b>		
<b>Item</b>	<b>B mm</b>	<b>Finish</b>
BAR600ASN270	60	AS - Silver

<b>baseboard &gt;&gt; BAI Internal corner in Plastic</b>		
<b>Item</b>	<b>B mm</b>	<b>Finish</b>
BAI600PS	60	PS - Silver

<b>baseboard &gt;&gt; BAE External corner in Plastic</b>		
<b>Item</b>	<b>B mm</b>	<b>Finish</b>
BAE600PS	60	PS - Silver

<b>baseboard &gt;&gt; BAT End cap in Plastic</b>		
<b>Item</b>	<b>B mm</b>	<b>Finish</b>
BAT600PSSETDS	60	PS - Silver

## APPLICATION

1. Check that the substrate is solid, flat, clean, degreased and dry, verifying that the application temperature is not lower than 15°C in case of gluing;
2. Cut the profile to the required length;
3. Apply the adhesive (FIXXTEC) to the part of the profile to be adhesived, or remove the protective paper from the adhesive for self-adhesive versions, and position the profile correctly without further adjustments;
4. Apply the profile with uniform pressure without hammering;
5. Remove any adhesive residue from the profile immediately.

N.B.: Aluminum profiles offer limited resistance to alkaline substances, so their use must be evaluated according to the expected chemical aggressions. Aluminum profiles in contact with cementitious substances can be attacked by corrosion processes, so residues of used adhesives and sealants should be removed immediately. When laying, the right amount of adhesive must be used and the right drying times observed, avoiding creating cavities in which water can stagnate, which would lead to the formation of alkaline substances (aluminum hydroxide) and trigger corrosive electrolytic phenomena.

## CLEANING AND MAINTENANCE

### ALUMINUM:

Aluminum requires no special maintenance.

For cleaning, use colorless alcohol diluted in water or neutral detergents, avoiding acidic ones (e.g., hydrochloric or hydrofluoric acid); use non-abrasive sponges or cloths to avoid damage. We recommend not applying cleaners directly to surfaces. After cleaning, rinse with water and dry immediately with a soft cloth. Avoid polishes. Quickly remove residual cement or grout to protect the surface.

## WARNINGS

These profiles must be handled with care, taking care to use cut-resistant gloves. The instructions and requirements contained herein, while based on our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for use and assumes all responsibility for any damage resulting from incorrect installation of the material.

## BILL OF QUANTITIES ITEM

Supply and installation of profile in \_\_\_\_\_ (material), with finish \_\_\_\_\_  
\_\_\_\_\_ (see Material Description section) of characteristic size \_\_\_\_\_ mm, as a floor closing  
profile and protection of the perimeter expansion joint.

Family type \_\_\_\_\_ of the Profilitec company as a skirting board profile to be supplied and installed  
properly, following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: \_\_\_\_\_

Material: \_\_\_\_\_ €/m

Installation: \_\_\_\_\_ €/m

Total price: \_\_\_\_\_ €/m