

## COFLEX CF


### PRODUCT DESCRIPTION



COFLEX CF mortar bed movement joints in co-extruded synthetic resin are conceived to subdivide large tile bays. Exclusively suitable for pedestrian traffic, this profile provides limited protection to the tile edges and compensates slight differential movement due to substrate contraction and expansion. They are installed with thin-set mortar. Ideally used in retail shops, hotels, sports facilities and schools

### TECHNICAL FEATURES

Length: 2,70 meters



Coextruded Synthetic Resinil + Resinflex

B = 8 mm

### MATERIAL DESCRIPTION

#### Coextruded Synthetic Resinil + Resinflex

RESINIL Thermoplastic synthetic resin for COEXTRUSION:

Made from primary resin whose composition based on Polyvinyl Chloride characterizes it for high resistance and optimized compatibility with regards to long-lasting adhesion with plasticized resins used in the coextrusion process, i.e. the permanent union of two materials with different degrees of Shore hardness.

RESINFLEX Plasticized thermoplastic synthetic resin:

Made from primary resin, its polyvinyl chloride composition provides high resistance and compatibility with Resinil in the COEXTRUSION process we use in most expansion joints. Thanks to the nature of the plasticizers used, the material maintains its essential elasticity characteristics over time.



P23

coflex >> CF in PVC		
Item	H mm	Finish
CF230P10270	23	P10 - Transparent
CF350P10270	35	P10 - Transparent
CF450P10270	45	P10 - Transparent
CF230P23270	23	P23 - Cement Grey
CF350P23270	35	P23 - Cement Grey
CF450P23270	45	P23 - Cement Grey



## APPLICATION

1. Cut the profile to the required length;
2. Make sure the groove or joint you're filling is the right size for the profile to fit into. Generally, for wooden floors, calculate 0.5 mm less than the joint; for stone and ceramic floors, the measurement is the joint's size.
3. Apply the adhesive (FIXXTEC) in the groove;
4. Position the profile by inserting it with uniform pressure and using a rubber mallet;
5. Remove any adhesive residue from the profile immediately.

## CLEANING AND MAINTENANCE

### SYNTHETIC RESIN:

Thermoplastic synthetic resin does not require any special maintenance.

It can be easily cleaned with colorless alcohol diluted in water or with normal detergents, provided they are not acid-based, also diluted in water; rinse with water only. Use non-abrasive sponges or cloths to avoid scratching the surface.

## WARNINGS

The indications and specifications contained herein, while consistent with our experience, are intended to be purely indicative and require confirmation through extensive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

## BILL OF QUANTITIES ITEM

Supply and installation of profile in \_\_\_\_\_ (material), with finish \_\_\_\_\_  
 \_\_\_\_\_ (see Material Description section) of characteristic size \_\_\_\_\_ mm, equipped with a conical lateral surface with undercut teeth that guarantee a perfect grip when cutting the screed and with an elastic internal part for better control of expansions in compression.

Family type \_\_\_\_\_ from the Profilitec company as an elastic fractioning and protection joint for the covering to be supplied and installed properly, following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: \_\_\_\_\_

Material: \_\_\_\_\_ €/m

Installation: \_\_\_\_\_ €/m

Totale price: \_\_\_\_\_ €/m

**Profilitec S.p.A.**  
 Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY  
 Tel: +39 0444 268311  
 e-mail: profilitec@profilitec.com

**Profilitec Corp.**  
 e-mail: customerservice@profilitec.com

**Profilitec Ibérica, S.L.U.**  
 e-mail: iberica@profilitec.com

**Profilitec France**  
 e-mail: france@profilitec.com