

SANITEC ER


PRODUCT DESCRIPTION



SANITEC ER Internal corner cove-shaped profiles are easy to clean and designed to meet hygiene standards in public spaces subject to sanitary inspection, such as hospitals, food processing plants and industrial kitchens. Installed on site prior to the wall and floor coverings, the profile perfectly integrates into the corner detail.

TECHNICAL FEATURES

Length: 2,70 meters



Synthetic Colormassa Resinil

R = 16 mm

H1 = 15 mm

MATERIAL DESCRIPTION

Synthetic Colormassa Resinil

RESINTOP Rigid thermoplastic synthetic resin:

This material is specifically formulated to optimize the performance of rigid profiles intended for permanent indoor and outdoor applications, where both aesthetic and durability requirements must be met. Produced from primary resin with a Polyvinyl Chloride (PVC)-based composition, it is suitable for a wide range of uses at temperatures up to +60°C. The selected raw material ensures excellent resistance to UV rays, limited mechanical impacts, and strong protection against the stagnation of fungi and bacteria.



P11



P22

| sanitec >> ER Synthetic Resin Full Body Colored Resinil | | |
|---|------|-------------------|
| Item | H mm | Finish |
| ER9P11270 | 9 | P11 - Pure White |
| ER11P11270 | 11 | P11 - Pure White |
| ER9P22270 | 9 | P22 - Pastel Grey |
| ER11P22270 | 11 | P22 - Pastel Grey |

| sanitec >> ERI Internal Corner Junction synthetic resin | | |
|---|------|-------------------|
| Item | H mm | Finish |
| ERIP11SET | X | P11 - Pure White |
| ERIP22SET | X | P22 - Pastel Grey |

| sanitec >> ERE External Corner Junction in Synthetic Resin | | |
|--|------|-------------------|
| Item | H mm | Finish |
| EREPI1SET | X | P11 - Pure White |
| EREPI2SET | X | P22 - Pastel Grey |

| sanitec >> ERF End cap in Synthetic Resin | | |
|---|------|-------------------|
| Item | H mm | Finish |
| ERFP11SET | X | P11 - Pure White |
| ERFP22SET | X | P22 - Pastel Grey |

| sanitec >> ERT Three-way Junction in Synthetic Resin | | |
|--|------|-------------------|
| Item | H mm | Finish |
| ERTP11SET | X | P11 - Pure White |
| ERTP22SET | X | P22 - Pastel Grey |

APPLICATION

1. Choose a profile according to tile thickness and desired finish;
2. Cut to the desired length;
3. Spread the adhesive in the profile application area with the help of a notched trowel;
4. Position the profile by pressing it so that it is embedded in it, and then spread the resulting excess adhesive on the surface of the flap;
5. Lay the tiles, taking care to align them with the profile and leave a gap of about 2 mm. The profile laid properly should be installed in the same plane as the tile;
6. To apply special pieces such as external and internal corners, joints, and end caps, use a specific, long-lasting flexible adhesive such as FIXXTEC. Before application, make sure the joint surface is free of grease or similar substances, which could compromise proper bonding;
7. Clean any glue residue from the profile before it dries. Thoroughly seal joints between profile and tile.

CLEANING AND MAINTENANCE

SYNTHETIC RESIN:

Thermoplastic synthetic resin does not require any special maintenance.

It can be easily cleaned with colorless alcohol diluted in water or with normal detergents, provided they are not acid-based, also diluted in water; rinse with water only. Use non-abrasive sponges or cloths to avoid scratching the surface.

WARNINGS

These profiles should be handled with care, using cut-resistant gloves. The indications and prescriptions herein, while corresponding to our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines any responsibility for any damage to people or things resulting from improper use of the products. The user is required to determine whether or not the product is suitable for use and assumes all responsibility arising from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____ (see Material Description section) of characteristic size _____ mm, with concave sanitary cove function and a curvature radius of 16 mm.

Profile family type _____ of Profilitec company as a closing and protection profile for the covering, to be supplied and installed in a professional manner, respecting the methods and application fields indicated by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ €/m

Installation: _____ €/m

Total price: _____ €/m