

SANITEC IC25


PRODUCT DESCRIPTION



Conceived as hygienic wall-to-wall or wall-to-floor transitions, SANITEC IC cove-shaped profiles meet hygiene standards in public spaces subject to sanitary inspection, such as hospitals, food processing plants, industrial kitchens and public bathrooms. Ideal for retrofit applications in public building renovations. The slightly rounded edges seal the profile onto the surface. Use our adhesive for on-site installation. The H=60mm version also acts as a baseboard.

TECHNICAL FEATURES

Length: 2,70 meters



Stainless Steel

R = 16 mm

MATERIAL DESCRIPTION

Stainless Steel

Steel profiles are made by cold forming sheets of constant thickness, thus differing from the corresponding aluminum and brass versions made by hot extrusion, while maintaining their application and dimensional characteristics. Stainless steel effectively resists high mechanical stress and is particularly suitable for use in the chemical, food, and hospital sectors, where hygiene, durability, and chemical resistance are essential. Normally produced with a semi-gloss finish, a brushed finish can also be achieved by partially removing material using rotating nylon and quartz fiber brushes. This process gives the surface a matte appearance without altering its characteristics.

AISI 304 STAINLESS STEEL - EN X 5 CrNi 18 10 - DIN 1.4301:

This steel belongs to the AUSTENITIC category and is the most widespread and commonly used alloy for products requiring high technical and performance characteristics. It is highly resistant to most chemical agents but may stain or darken superficially; a standard polishing product is sufficient to restore its original appearance.



IL

| sanitec >> IC25 in Stainless Steel AISI 304 - DIN 1.4301 | | |
|--|------|-------------|
| Item | B mm | Finish |
| IC25ILN270 | 25 | IL-Polished |

| sanitec >> ICI/ICE/ICT Junctions in Stainless Steel AISI 304 - DIN 1.4301 | | |
|---|------|-----------------------------|
| Item | B mm | Finish |
| ICI25ILNSET2 | X | IL-Polished internal corner |
| ICE25ILNSET2 | X | IL-Polished external corner |
| ICT25ILNSET2 | X | IL-Polished Three-way |

APPLICATION

1. Check that the substrate is solid, flat, clean, degreased and dry, verifying that the application temperature is not lower than 15°C in case of gluing;
2. Cut the profile to the required length;
3. Apply the adhesive (FIXXTEC) to the part of the profile to be adhesived, or remove the protective paper from the adhesive for self-adhesive versions, and position the profile correctly without further adjustments;
4. Apply the profile with uniform pressure without hammering;
5. Remove any adhesive residue from the profile immediately.

CLEANING AND MAINTENANCE

STAINLESS STEEL:

Stainless steel is easy to clean and very hygienic because of its smooth, nonporous surface, which hinders the growth of bacteria. To keep it in good condition, simply wash it with warm soapy water, rinse it thoroughly and dry it with a soft cloth. If exposed to weathering, periodic cleaning is recommended to prevent corrosion. Brushed surfaces should be cleaned in the direction of brushing. In case of scratches, a specific polish can be used with a soft cloth. Avoid cleaning agents containing hydrochloric acid, hydrofluoric acid or bleach, as well as abrasive products. Do not leave ordinary steel objects in contact with stainless steel to prevent contamination and rust stains. Also, do not leave damp patches or sponges on the surface to prevent water halos.

WARNINGS

These profiles must be handled with care, taking care to use cut-resistant gloves. The instructions and requirements contained herein, while based on our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
_____ (see Material Description section) of characteristic size _____ mm, with connecting curvature.

Family type _____ from the Profilitec company as a concave sanitary cove to be applied as a connection between the wall and the bathtub or shower, to be supplied and installed properly, following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ €/m

Installation: _____ €/m

Total price: _____ €/m