

## SANITEC IC60


### PRODUCT DESCRIPTION



SANITEC IC60 is a range of resin baseboards created for hygienic connections between floor and wall covering or between two walls, particularly in the healthcare, chemical and food fields. Designed for application on existing surfaces, they can be used for renovations and retrofitting of previously built public buildings, because they meet current regulations. Shaped outer edges ensure perfect adhesion of the profile to the substrate.

### TECHNICAL FEATURES

Length: 2,70 meters



PVC

H1 = 20 mm

### MATERIAL DESCRIPTION

#### PVC

RESINTOP Rigid thermoplastic synthetic resin:

This material is specifically formulated to optimize the performance of rigid profiles intended for permanent indoor and outdoor applications, where both aesthetic and durability requirements must be met. Produced from primary resin with a Polyvinyl Chloride (PVC)-based composition, it is suitable for a wide range of uses at temperatures up to +60°C. The selected raw material ensures excellent resistance to UV rays, limited mechanical impacts, and strong protection against the stagnation of fungi and bacteria.

P11

sanitec >> IC60 in Synthetic Resin Full body Colored Resintop		
Item	B mm	Finish
IC60P11270	60	P11 - Pure White

## APPLICATION

1. Check that the substrate is solid, flat, clean, degreased and dry, verifying that the application temperature is not lower than 15°C in case of gluing;
2. Cut the profile to the required length;
3. Apply the adhesive (FIXXTEC) to the part of the profile to be adhesived, or remove the protective paper from the adhesive for self-adhesive versions, and position the profile correctly without further adjustments;
4. Apply the profile with uniform pressure without hammering;
5. Remove any adhesive residue from the profile immediately.

## CLEANING AND MAINTENANCE

### SYNTHETIC RESIN:

Thermoplastic synthetic resin does not require any special maintenance.

It can be easily cleaned with colorless alcohol diluted in water or with normal detergents, provided they are not acid-based, also diluted in water; rinse with water only. Use non-abrasive sponges or cloths to avoid scratching the surface.

## WARNINGS

These profiles must be handled with care, taking care to use cut-resistant gloves. The instructions and requirements contained herein, while based on our experience, are to be considered purely indicative and must be confirmed by exhaustive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for use and assumes all responsibility for any damage resulting from incorrect installation of the material.

## BILL OF QUANTITIES ITEM

Supply and installation of profile in \_\_\_\_\_ (material), with finish \_\_\_\_\_  
\_\_\_\_\_ (see Material Description section) of characteristic size \_\_\_\_\_ mm, with connecting curvature.

Family type \_\_\_\_\_ from the Profilitec company with the dual function of concave sanitary cove and floor closing profile and protection of the perimeter expansion joint to be applied as a connection between the wall and the bathtub or shower, to be supplied and installed according to the rules of the art, respecting the methods and fields of application indicated by the manufacturer.

Profile length: 2700 mm

Profile SKU: \_\_\_\_\_

Material: \_\_\_\_\_ €/m

Installation: \_\_\_\_\_ €/m

Total price: \_\_\_\_\_ €/m