

WALLPROTECTION WB


PRODUCT DESCRIPTION



Synthetic resin skirting, through body colored to hide the effects of wear and damage. The smooth surface makes it easy to clean and more hygienic than traditional skirtings. Available in colors and a range of dual-colored options. For sanitary benefits, the profile is coved which will allow for it to be "set-in" to the flooring using a cold weld procedure for a totally homogeneous finish. Thanks to the particular material composition and to the specific cavity at the bottom, this skirting can also be chemically welded to the PVC floor, as often required by hygiene standards. The WB skirting profile can be coordinated with the other profiles in the wallprotection range - corner protectors (WA) and bumper guards (WP).

TECHNICAL FEATURES

Length: 2,70 meters



Synthetic resin

H1 = 15,8 mm

MATERIAL DESCRIPTION

Synthetic Resin

RESINIL Thermoplastic synthetic resin for COEXTRUSION:

Made from primary resin whose composition based on Polyvinyl Chloride characterizes it for high resistance and optimized compatibility with regards to long-lasting adhesion with plasticized resins used in the coextrusion process, i.e. the permanent union of two materials with different degrees of Shore hardness.

RESINFLEX Plasticized thermoplastic synthetic resin:

Made from primary resin, its polyvinyl chloride composition provides high resistance and compatibility with Resinil in the COEXTRUSION process we use in most expansion joints. Thanks to the nature of the plasticizers used, the material maintains its essential elasticity characteristics over time.

| wallprotection >> WB in Synthetic Resin Full body Colored Resintop | | |
|--|------|---------------------------|
| Item | B mm | Finish |
| WB100P11/22270 | 100 | P11 - White + Pastel Grey |
| WB100P11/11270 | 100 | P11 - White + Pure White |
| WB100P22/22270 | 100 | P22 - Grey + Pastel Grey |

APPLICATION

1. Check that the substrate is solid, flat, clean, degreased and dry, verifying that the application temperature is not lower than 15°C in case of gluing;
2. Cut the profile to the required length;
3. Apply the adhesive (FIXXTEC) to the part of the profile to be adhesived, or remove the protective paper from the adhesive for self-adhesive versions, and position the profile correctly without further adjustments;
4. Apply the profile with uniform pressure without hammering;
5. Remove any adhesive residue from the profile immediately.

CLEANING AND MAINTENANCE

SYNTHETIC RESIN:

Thermoplastic synthetic resin does not require any special maintenance.

It can be easily cleaned with colorless alcohol diluted in water or with normal detergents, provided they are not acid-based, also diluted in water; rinse with water only. Use non-abrasive sponges or cloths to avoid scratching the surface.

WARNINGS

The indications and specifications contained herein, while consistent with our experience, are intended to be purely indicative and require confirmation through extensive practical applications. Profilitec declines all responsibility for any damage to persons or property resulting from improper use of the product. The user is responsible for determining whether or not the product is suitable for the intended use and assumes all responsibility for any damage resulting from incorrect installation of the material.

BILL OF QUANTITIES ITEM

Supply and installation of profile in _____ (material), with finish _____
_____ (see Material Description section) with characteristic size _____ mm, skirting board
with shockproof and self-extinguishing characteristics.

Family type _____ from the Profilitec company with the function of skirting board and protection against
impacts and two-tone finishing of the covering or floor to protect the perimeter expansion joint to be applied on coverings,
to be supplied and installed properly following the methods and fields of application suggested by the manufacturer.

Profile length: 2700 mm

Profile SKU: _____

Material: _____ €/m

Installation: _____ €/m

Total price: _____ €/m