
CARPETEC trim profiles compress to hold flexible flooring, such as natural fiber fibre carpeting. By pressing the profiles, they close slightly to clamp the flooring, hiding and protecting edge imperfections.

carpe (ec





CARPETEC MA 24 A*Self-Adhesive Anodized Aluminum

Self-adjusting trim profile. The self-adhesive strip underneath the profile guarantees fast, strong and lasting grip without adding floor thickness.



| | B = in | mm | | Art. | |
|--|--------|----|----|------|-----|
| Material: | 15/16 | 24 | MA | 24 | ASA |
| Extruded Anodized | 15/16 | 24 | MA | 24 | AOA |
| Aluminum | 15/16 | 24 | MA | 24 | ABA |
| Length: 8'10" (2.70 meters) ☐: 35-7/16" / 4' 5" (0.90 / 1.35 meters) | | | | | |

CARPETEC MS 26 A* Anodized Aluminum

The narrow top surface of this self-adjusting trim profile is ideal for discreet installations. The self-adhesive strip underneath the profile guarantees fast, strong and lasting grip without adding floor thickness.

Available in two versions: self-adhesive and pre-drilled.

| 43/64" (17mm) |
|----------------|
| 1-1/32" (26mm) |

| Material: | 1-1/32 | 26 | MS | 26 | ASF/A |
|-----------------------------|--------|----|----|----|-------|
| Extruded Anodized | 1-1/32 | 26 | MS | 26 | AOF/A |
| Aluminum | 1-1/32 | 26 | MS | 26 | ABF/A |
| Length: 8'10" (2.70 meters) | | | | | |

CARPETEC MS 26 OLN Polished Brass

Due to the intrinsic qualities of the material, this classic, solid brass profile guarantees resistance to chemical and mechanical impact and is suitable for elegant interior detailing.

| 71/16, 1844ml |
|---------------|
| 29/32" (23mm) |

| Material: Extruded Brass | 1-1/32 | 26 | MS | 26 | OLN |
|---|--------|----|----|----|-----|
| Finish: Polished (OLN) | | | | | |
| Length: 8'10" (2.70 meters) (2.70 meters) (35-7/16" / 4' 5" (0.90 / 1.35 meters) | | | | | |

CARPETEC MD 43 A*F Anodized Aluminum - Pre-drilled


The wide profile base makes it ideal as edge trimming for area carpeting and walkways. The base can also be fitted with self-adhesive tape that temporarily holds the profile in place.

| NITE THERM |
|-----------------|
| 1-11/16" (43mm) |

| Ī | Material: | 1-11/16 | 43 | MD | 43 | ASF |
|------------|----------------------------|---------|----|----|----|-----|
| | Extruded Anodized | 1-11/16 | 43 | MD | 43 | AOF |
| , | Aluminum | 1-11/16 | 43 | MD | 43 | ABF |
| = 1 | Length: 8'10" (2.70meters) | | | | | |

CARPETEC MD 43 A*D Anodized Aluminum - Toothed

The toothed profile base is optimal for gripping stretched carpet.



| Material: | 1-11/16 | 43 | MD | 43 | ASD |
|----------------------------|---------|----|----|----|-----|
| Extruded Anodized | 1-11/16 | 43 | MD | 43 | AOD |
| Aluminum | 1-11/16 | 43 | MD | 43 | ABD |
| Length: 8'10" (2.70meters) | | | | | |

 $[\]triangle$: Pre-cut length available in SELFLINE kit L = 35-7/16" / 4' 5" (0.90/1.35m)