


Designed for carpet flooring, **CARPETEC MG** profiles are composed of two elements: a base track onto which the carpet is laid, and an interlocking, grooved top piece that snaps shut and compresses the carpeting.

carpetec MG



CARPETEC MG 25 A*N Anodized Aluminum Top

This anodized aluminum profile is available in three finishes: silver (AS), gold (AO), bronze (AB). Due to the chromatic variations available, it is especially suited for residential use.

CARPETEC MG 25 OLN Polished Brass Top

Due to the intrinsic qualities of the material, this brass profile guarantees high resistance to chemical and mechanical impact, corrosion and wear.

CARPETEC MGB 25 AN* Natural Aluminum Base Track

Drilled base track for glued carpeting, to be installed with flathead screws, code F. Toothed base track for stretched carpeting, code D.

	B = in	mm	Art.		
Material:	1	25	MG	25	ASN
Extruded Anodized Aluminum	1	25	MG	25	AON
Finish*: Silver (AS), Gold (AO), Bronze (AB)	1	25	MG	25	ABN
Length: 8'10" (2.70meters)					

Material:	1	25	MG	25	OLN
Extruded Brass					
Finish: Polished (OLN)					
Length: 8'10" (2.70meters)					

Material:	1-11/16	43	MGB	25	ANF
Aluminum	1-11/16	43	MGB	25	AND
Finish: Natural (AN*)					
Length: 8'10" (2.70meters)					