

INTERJOLLY IJ profiles optimize wall-to-floor tile transitions while allowing differential movement. The perforated flange installed behind the wall tiling guarantees secure grip. This cove-shaped profile is hygienic, easy to clean and can replace silicone caulking around shower stalls and bathtubs.









INTERJOLLY IJ-P* Solid Extruded Synthetic Resin

Extruded as solid synthetic resin, this profile is not simply color-coated; the color is fully embedded in the body of the profile and is available in a vast color range suitable in diverse design settings. This trim profile is easy to cut, saving time and money in the installation process and guaranteeing impeccably durable results. The profile is UV and scratch resistant, tolerant to mechanical impact and most domestic cleaning products.

INTERJOLLY IJ-IL Polished Stainless Steel AISI 304 - DIN 1.4301

This stainless steel profile ensures good resistance to mechanical impact and high resistance to corrosion from most diluted chemicals found in laboratories and aggressive detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, public bathrooms and hospitals. Internal (ICI), external (ICE) and three-way (ICT) joint pieces are available.

	Color	H = 19/64" (7.5mm)			
Material: Resintop	11= Pure White	IJ	75	P11	
	12=White	IJ	75	P12	
Length: 8'10" (2.70meters)	22= Grey	IJ	75	P22	
	31= Bahama Beige	IJ	75	P31	
	Color	H = 3/8" (9.5mm)			
Meterial: Pecinten	11= Pure White	- 11	0.5	D11	
Motorial Posinton	II = Pure white	IJ	95	P11	
Material: Resintop	11= Pure White	IJ	95 95	P11 P12	
Material: Resintop Length: 8'10" (2.70meters)					

	H = in	mm		Art.	
Material: Stainless steel AISI 304	5/16 3/8	8 10	IJ IJ	80 100	IL IL
Finish: Polished (IL)					
Length: 8'10" (2.70meters)					