





KERAJOLLY profiles are designed to define sharp external wall corners and prevent chipping and cracking of fragile single-fired ceramic tiles. They are easy to install, simply choose the size of the profile according to the tile thickness.

kerajolly KJ



(TR 100* - KJ 100*)



KERAJOLLY TR-I* Stainless steel AISI 304 - DIN 1.4301 and AISI 316

This stainless steel profile ensures high resistance to most diluted chemicals found in laboratories and aggressive detergents present in food processing plants, commercial kitchens, hospitals and laboratories. The AISI 316 standard version (code ILM) is recommended for marine environments and swimming pools.

Available in polished (IL), brushed (IS) and sanded (IX) stainless steel.

	H = in	mm	Art.		
Material: Stainless steel AISI 304	3/16	4.5	TR	45	IL/IS
Stainless steel AISI 316 (ILM)	1/4	6	TR	60	IL/IS/ILM
Finish: Polished (IL), Brushed (IS), Sanded (IX)	5/16	8	TR	80	IL/IS/ILM
	3/8	10	TR	110	IL/IS/IX/ILM
Length: 8'10" (2.70meters)	1/2	12.5	TR	125	IL/IS/IX/ILM
☒ "thin" line					

KERAJOLLY TR-KJ A* Anodized Aluminum

This profile has a silver (AS), titanium (AT), copper (AR) or gold (AO) coating which offers adequate resistance to corrosion.

Material: Extruded Anodized Aluminum	3/32	2	TR	20	AS	-	-	-
	1/8	3	TR	30	AS	-	-	-
Finish: Silver (AS), Titanium (AT), Copper (AR), Gold (AO)	3/16	4.5	TR	45	AS	-	-	-
	1/4	6	TR	60	AS	KJ	60	AT/AR
	5/16	8	TR	80	AS	KJ	80	AT/AR
Length: 8'10" (2.70meters)	3/8	10	TR	100	AS	KJ	100	AT/AR/AO
☒ "thin" line								
	1/2	12.5	TR	125	AS	KJ	125	AT/AR

KERAJOLLY KJ-A*B Bright Polished Aluminum

The elegant polished surface finish of this profile, available in bright polished chrome (KJ*ASB), titanium (KJ*ATB), and gold (KJ*AQB), is highly resistant to oxidation and especially suited for matching polished bathroom accessories.

Material: Extruded Anodized Aluminum	1/4	6	KJ	60	ASB/AQB
	5/16	8	KJ	80	ASB/ATB/AQB
Finish: Bright polished chrome (ASB), Bright polished titanium (ATB), Bright polished gold (AQB)	3/8	10	KJ	100	ASB/ATB/AQB
	1/2	12.5	KJ	125	ASB/ATB/AQB
Length: 8'10" (2.70meters)					



KERAJOLLY trim profiles protect ceramic tiled wall corners against impact while guaranteeing safety standards and durability. The **KERAJOLLY** color range can also be matched with **LISTEC** decorative strips, proposing endless design possibilities.

KERAJOLLY KJ-A* Powder Coated Aluminum

This aluminum profile is color-coated with a polyurethane powder coat that is UV-resistant and guarantees tolerance to most domestic cleaning products and weathering. The rigid, straight profiles serve as a guideline for tile laying along imperfect wall surfaces.

	Color	H = 1/4" (6mm)			H = 5/16" (8mm)				
Material: Powder coated Aluminum	11= Pure White	KJ	60	A	11	KJ	80	A	11
	12= White	KJ	60	A	12	KJ	80	A	12
	21= Light Grey	KJ	60	A	21	KJ	80	A	21
	22= Grey	KJ	60	A	22	KJ	80	A	22
	23= Cement Grey	KJ	60	A	23	KJ	80	A	23
	31= Bahama Beige	KJ	60	A	31	KJ	80	A	31
	32= Dark Beige	KJ	60	A	32	KJ	80	A	32
	41= Cream	KJ	60	A	41	KJ	80	A	41
	42= Ivory	KJ	60	A	42	KJ	80	A	42
	51= Black	KJ	60	A	51	KJ	80	A	51
Length: 8'10" (2.70meters)									

	Color	H = 3/8" (10mm)			H = 1/2" (12.5mm)				
Material: Powder coated Aluminum	11= Pure White	KJ	100	A	11	KJ	125	A	11
	12= White	KJ	100	A	12	KJ	125	A	12
	21= Light Grey	KJ	100	A	21	KJ	125	A	21
	22= Grey	KJ	100	A	22	KJ	125	A	22
	23= Cement Grey	KJ	100	A	23	KJ	125	A	23
	25= Emb.Cement Grey	KJ	100	A	25	-	-	-	-
	31= Bahama Beige	KJ	100	A	31	KJ	125	A	31
	32= Dark Beige	KJ	100	A	32	KJ	125	A	32
	33= Emb.Dove-Grey	KJ	100	A	33	-	-	-	-
	41= Cream	KJ	100	A	41	KJ	125	A	41
42= Ivory	KJ	100	A	42	KJ	125	A	42	
50= Emb. Micaceous	KJ	100	A	50	-	-	-	-	
51= Black	KJ	100	A	51	KJ	125	A	51	
Length: 8'10" (2.70meters)									

KERAJOLLY KJ-P* Full body Colored Synthetic Resin

Extruded as solid synthetic resin, this profile is not simply color-coated; the color is fully embedded in the body of the profile and is available in a vast color range suitable in diverse design settings. This trim profile is easy to cut, saving time and money in the installation process and guaranteeing impeccably durable results. The profile is scratch resistant, tolerant to mechanical impact and most domestic cleaning products.

	Color	H = 1/4" (6mm)			H = 5/16" (8mm)				
Material: Resintop	11= Pure White	KJ	60	P	11	KJ	80	P	11
	12= White	KJ	60	P	12	KJ	80	P	12
	21= Light Grey	KJ	60	P	21	KJ	80	P	21
	22= Grey	KJ	60	P	22	KJ	80	P	22
	23= Cement Grey	KJ	60	P	23	KJ	80	P	23
	31= Bahama Beige	KJ	60	P	31	KJ	80	P	31
	32= Dark Beige	KJ	60	P	32	KJ	80	P	32
	41= Cream	KJ	60	P	41	KJ	80	P	41
	42= Ivory	KJ	60	P	42	KJ	80	P	42
	51= Black	KJ	60	P	51	KJ	80	P	51
Length: 8'10" (2.70meters)									

	Color	H = 3/8" (10mm)			H = 1/2" (12.5mm)				
Material: Resintop	11= Pure White	KJ	100	P	11	KJ	125	P	11
	12= White	KJ	100	P	12	KJ	125	P	12
	21= Light Grey	KJ	100	P	21	KJ	125	P	21
	22= Grey	KJ	100	P	22	KJ	125	P	22
	23= Cement Grey	KJ	100	P	23	KJ	125	P	23
	31= Bahama Beige	KJ	100	P	31	KJ	125	P	31
	32= Dark Beige	KJ	100	P	32	KJ	125	P	32
	41= Cream	KJ	100	P	41	KJ	125	P	41
	42= Ivory	KJ	100	P	42	KJ	125	P	42
	51= Black	KJ	100	P	51	KJ	125	P	51
Length: 8'10" (2.70meters)									