





# stairtec SR

Practical and easy to clean, **STAIRTEC SR** can be used as stair nosing and trimming for all exposed edges. Its extended vertical edge conceals and protects the riser edge, preventing future cracking and chipping. The unique sectional design can match two different floor thicknesses with the same reversible profile. The patented section is designed with vertical dovetail anchoring.




Aluminum section



Aluminum and Brass section

(SR 8/15\*)



### TRIMTEC SR-O\* Brass

The vertical section of this brass profile protects delicate edges on ceramic stairs. Moisture and corrosive agents may oxidize the exposed surfaces. Buffing the profile with conventional polisher will bring back its shine in no time.

### TRIMTEC SR-AS Silver Anodized Aluminum

This profile has a silver coating, suitable for both indoor and outdoor application with high resistance to weathering and lower resistance to mechanical impact. During installation, excess adhesive and grout should be removed immediately to avoid stains. The exposed surface may change color or darken over time. Brass or stainless steel profiles are recommended in places of high wear and use.

### TRIMTEC SR-I\* Stainless Steel AISI 304 - DIN 1.4301

This stainless steel profile ensures high resistance to most diluted chemicals found in laboratories and aggressive detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, public toilets and hospitals. Available in polished (IL), brushed (IS) or sanded (IX) stainless steel.

|   | H/H1 = in                | mm                  | Art.     |                 |                |
|---|--------------------------|---------------------|----------|-----------------|----------------|
| Material: Brass                         | 5/16 / 9/16<br>3/8 / 1/2 | 8 / 15<br>10 / 12.5 | SR<br>SR | 8/15<br>10/12.5 | ON/OL<br>ON/OL |
| Finish: Natural (ON), Polished (OL)     |                          |                     |          |                 |                |
| Length: 8'10" (2.70meters)              |                          |                     |          |                 |                |
| Improved anchoring on the vertical side |                          |                     |          |                 |                |

|   |                          |                     |          |                 |          |
|---|--------------------------|---------------------|----------|-----------------|----------|
| Material: Extruded Anodized Aluminum    | 5/16 / 9/16<br>3/8 / 1/2 | 8 / 15<br>10 / 12.5 | SR<br>SR | 8/15<br>10/12.5 | AS<br>AS |
| Finish: Silver (AS)                     |                          |                     |          |                 |          |
| Length: 8'10" (2.70meters)              |                          |                     |          |                 |          |
| Improved anchoring on the vertical side |                          |                     |          |                 |          |

|                                     |                          |                     |          |                 |                |
|-------------------------------------|--------------------------|---------------------|----------|-----------------|----------------|
| Material: Stainless Steel AISI 304  | 5/16 / 9/16<br>3/8 / 1/2 | 8 / 15<br>10 / 12.5 | SR<br>SR | 8/15<br>10/12.5 | IL/IS<br>IL/IS |
| Finish: Polished (IL), Brushed (IS) |                          |                     |          |                 |                |
| Length: 8'10" (2.70meters)          |                          |                     |          |                 |                |

### CURVELINE

The **TRIMTEC TR** series is also available with a specially-cut flange that allows shaping for curved edges and inlays. To order: add the letter D to the product code. For further details see page 47.

