
Modern and sophisticated, STAIRTEC SWR stainless steel non-slip buttons are a safe and innovative alternative to linear profiles. The round, grooved buttons slightly protrude 1/16" (1.6mm) from the stair or floor surface. Elegantly designed, STAIRTEC SWR buttons can be used to customize wood and natural stone staircases. Installation and assembly can be made on or off-site.

To install on wood flooring, simply drill a 1/4" (6.5mm) hole and hammer the button in place. The buttons should be spaced 2-3/4" (70mm) on center.


To install natural wood or ceramic tile flooring, simply drill a 9/32" (7mm) hole and fasten the button with appropriate adhesive. The buttons should be spaced 2-3/4" (70mm) on center.



stairtec SWR







STAIRTEC SWR 25 IL Polished Stainless Steel AISI 303-DIN 1.4305

This stainless steel element which conforms to AISI 303 standards ensures elevated mechanical resistance and high resistance to most diluted chemicals found in laboratories and aggressive detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, public toilets and hospitals.

| | B = in | mm | | Art. | |
|--|--------|----|-----|------|----|
| Materiale: Stainless Steel AISI 303 | 1 | 25 | SWR | 25 | IL |
| Diameter: 1" (25mm) | | | | | |

