



Durable and safe carborundum mineral grain strips are priceless in accident prevention. **WALKTEC** ready-to-use adhesive strips can be applied to any surface. To enhance safety measures, we recommend applying double strips.

walk+tec SWH

INSTALLATION AND MAINTENANCE:

- 1) Thoroughly clean the stair surface of any grease, dirt and residue. Apply primer if necessary.
- 2) Round-off the strip ends.
- 3) Remove the adhesive backing and apply the strip uniformly with a hand roller.
- 4) In settings with temperatures below 15°, the strips and base must be preheated before application.
- 5) To maintain their non-slip properties, regularly sweep the strips clean.
- 6) To install on smooth tiles, score the tile before applying the strip.
- 7) Seal the strip edges as they may detach due to water infiltration.



WALKTEC SWH Carborundum Mineral Grain Strips

To guarantee high performance, the mineral grain strips are composed of a heavy-duty adhesive covered with highly-resistant and durable abrasive granules. The adhesive is protected by a removable backing. In high traffic areas, **WALKTEC SWH** strips can withstand up to 1.3 million steps. The product is supplied in 60' (18.3m) rolls (SWHS is sold in 24" - 61cm strips).

	inxft	mmxm	Art.		Colour	
Material: Carborundum	3/4x60	19x18.3	SWH	19	CF	Fluoresc.
	3/4x60	19x18.3	SWH	19	C51	Black
Widths: 3/4", 1", 2" (19, 25, 50mm)	1x60	25x18.3	SWH	25	C51	Black
	1x60	25x18.3	SWH	25	C10	Transp.
	1x60	25x18.3	SWH	25	C11	White
	2x60	50x18.3	SWH	50	C51	Black
	3/4x24	19x0.61	SWHS	19	C51	Black