




zerotec ZRM

ZEROTEC ZRM profile is the ideal solution for joining two floors at different levels, between a ceramic covering and one in moquette carpeting for instance. This trim allows a 3/16" - 5 mm progressive sloping difference to the next floor to match thus making safer when treading over the connecting floors. The ramp inclination has been conceived for vehicle and wheel carts transit.



(ZRM 100 IL)



ZEROTEC ZRM-IL Polished Stainless Steel AISI 304 - DIN 1.4301

This stainless steel profile is an AISI 304 standard which ensures high tolerance to most of diluted chemicals found in laboratories or strong detergents present in food processing plants, commercial kitchens, hospitals, public toilets, slaughter houses, breweries, etc.

ZEROTEC ZRM-AS Anodized Aluminum

Profile available in anodized aluminum with a silver surface finish (AS).

ZEROTEC ZRM-ATSB Brushed Polished Anodized Aluminum

Profile available in anodized aluminum with a Brushed Polished Titanium (Nickel) surface finish (ATSB)

ADA compliant products

	H = in	mm	B = in	mm	Art.		
Material:	5/16	8	15/32	12	ZRM	80	IL
Stainless Steel AISI 304	3/8	10	9/16	15	ZRM	100	IL
Finish: Polished (IL)	1/2	12.5	11/16	17.5	ZRM	125	IL
Length: 8'10" (2.70 meters)							

	H = in	mm	B = in	mm	Art.		
Material:	5/16	8	5/8	16	ZRM	80	AS
Anodized Aluminum	3/8	10	7/8	22.3	ZRM	100	AS
Finish: Silver (AS)	1/2	12.5	1-3/64	26.6	ZRM	125	AS
Length: 8'10" (2.70 meters)							

	H = in	mm	B = in	mm	Art.		
Material:	3/8	10	7/8	22.3	ZRM	100	ATSB
Anodized Aluminum							
Finish: Brushed Polished Titanium (Nickel) (ATSB)							
Length: 8'10" (2.70 meters)							