

SHOWERTEC STKPV

PRODUCT DESCRIPTION



Showertec STKPV


The SHOWERTEC STK range includes a series of profiles dedicated to the shower area. They are products designed to simplify the installation phase. STKPV profiles act as a transition between the sloping tiled shower tray and the floor when you want to install the glass wall as well. The latter can be combined with its STKF front profile and with the STKV glass holder profile mounted on the cladding in order to achieve safe assembly of the glass shower wall and to obtain a homogeneous and optimal finish thanks to the clean line of the installation. The Showertec STK profiles create bathroom environments with a minimalist and modern design, obtaining floor-level showers without obstacles and without architectural barriers.

Available in right and left version.

STKP profiles act as transition profiles between the sloped and tiled shower tray and the floor when the glass partition is also installed.

TECHNICAL FEATURES

Lengths: 1,35 m - 2,00 m



Article	HxB mm	Material	Finish	Pc
STKPV35IS135DX	10x35	Stainless Steel	Brushed	1
STKPV35IS135SX	10x35	Stainless Steel	Brushed	1
STKPV48IS200DX	10x48	Stainless Steel	Brushed	1
STKPV48IS200SX	10x48	Stainless Steel	Brushed	1

APPLICATION

1. Cut the profile STKPV at the desired length;
2. Apply the tile adhesive to the surface where the profile will be laid and position it by pressing it so that it is embedded in;
3. Lay the tiles spreading the adhesive over the entire surface using the full bed technique and taking care to leave a 2mm joint;
4. Clean any glue residue from the profile before it dries;
5. Grout carefully covering all the joints and clean the profile of all residues before they dry.

CLEANING AND MAINTENANCE

Do not use abrasive detergents for cleaning.
The profile does not require any particular care or maintenance.

