

**TR-KJ**

**PRODUCT DESCRIPTION**



**TR-KJ**

Resilient materials are commonly used for floors and walls as well as over existing flooring.

For thinner flooring materials, we recommend **profiles** that can be solidly anchored and provide maximum **edge protection**.

**TR** and **KJ** family of profiles meets these needs by providing a **solid base** with **tapered openings** for mechanical fastening or to be adhered using appropriate adhesive.

**TECHNICAL FEATURES**


**Length: 8'10" - 2.70 m**



**TR30:**

H= 1/8" - 3 mm


B= 1/8" - 3 mm



**TR45:**

H= 3/16" - 4.5 mm

B= 1/8" - 3 mm




**TR60:**

H= 1/4" - 6 mm

B= 1/8" - 3 mm

Article	Material	Finish	Pc
TR30ASF270	Anodized aluminum	AS - Silver	20
TR45ASF270	Anodized aluminum	AS - Silver	20
TR60ASF270	Anodized aluminum	AS - Silver	20
KJ30ATF270	Anodized aluminum	AT - Titanium	20
KJ45ATF270	Anodized aluminum	AT - Titanium	20
KJ60ATF270	Anodized aluminum	AT - Titanium	20

Article	Material	Finish	Pc
KJ30A65F270	Embossed painted aluminum	A65 - Matt black	20
KJ45A65F270	Embossed painted aluminum	A65 - Matt black	20
KJ60A65F270	Embossed painted aluminum	A65 - Matt black	20



AS AT A65

## APPLICATION

1. Select a profile height that matches the flooring material's thickness taking the adhesive into consideration;
2. Place the profile on the floor and mark its position;
3. For adhesive installation: apply bonding material to the underside of the base, press the profile in place and immediately remove excess bonding material;  
For mechanically fastened installation, use 1" long #4 flat head fasteners.
4. Be sure to remove any residual adhesive from the visible surface of the profile before curing.

## CLEANING AND MAINTENANCE

Do not use abrasive detergents for cleaning.  
The profile does not require any particular care or maintenance.