

ZLT

PRODUCT DESCRIPTION



ZLT

Resilient materials are commonly used for floors and walls as well as over existing flooring.


For thinner flooring materials, we recommend **profiles** that can be solidly anchored and provide maximum **edge protection**.

The **ZEROTEC** family of profiles meets these needs by providing a **solid base** with **tapered openings** for mechanical fastening or to be adhered using appropriate adhesive.

ZLT profiles provide sloped and ADA-compliant edge protection for resilient flooring materials of **different heights** ranging from 0 to up to 1/4" (6mm).

TECHNICAL FEATURES

Length: 8'10" - 2.70 m




ZLT30:

H= 1/8" - 3 mm

B= 1/4" - 6 mm

B1= 9/32" - 7 mm




ZLT50:

H= 3/16" - 5 mm

B= 1/4" - 6 mm

B1= 9/16" - 14 mm



ZLT60:


H= 1/4" - 6 mm

B= 7/16" - 11 mm

B1= 5/8" - 16 mm

Article	Material	Finish	Pc
ZLT30ASF270	Anodized aluminum	AS - Silver	20
ZLT50ASF270	Anodized aluminum	AS - Silver	20
ZLT60ASF270	Anodized aluminum	AS - Silver	20
ZLT30ATF270	Anodized aluminum	AT - Titanium	20
ZLT50ATF270	Anodized aluminum	AT - Titanium	20
ZLT60ATF270	Anodized aluminum	AT - Titanium	20

Article	Material	Finish	Pc
ZLT30A65F270	Embossed painted aluminum	A65 - Matt black	20
ZLT50A65F270	Embossed painted aluminum	A65 - Matt black	20
ZLT60A65F270	Embossed painted aluminum	A65 - Matt black	20



APPLICATION

1. Select a profile height that matches the flooring material's thickness taking the adhesive into consideration;
2. Place the profile on the floor and mark its position;
3. For adhesive installation: apply bonding material to the underside of the base, press the profile in place and immediately remove excess bonding material;
For mechanically fastened installation, use 1" long #4 flat head fasteners.
4. Be sure to remove any residual adhesive from the visible surface of the profile before curing.

CLEANING AND MAINTENANCE

Do not use abrasive detergents for cleaning.
The profile does not require any particular care or maintenance.