

Baseboard BAS

PRODUCT DESCRIPTION



BAS600AS

BAS baseboards are designed to meet modern minimalist design in which all elements perform their function by integrating with each other in a discreet but effective way. The profiles have a rectangular section available in 3 different heights to meet any aesthetic requirements.

BAS skirting boards also have a not visible groove at the bottom section to facilitate bonding and avoid adhesive smearing during installation. The baseboards have accessories that fit into the profile, creating corners and end caps with a smooth and pleasing effect of continuity.

TECHNICAL FEATURES



BAS*

H1= 13/32" - 10mm

BAS400: B= 1-9/16" - 40 mm

BAS600: B= 2-3/8" - 60 mm

BAS800: B= 3-1/8" - 80 mm

Article	Finish	pcs/pck
BAS400AS270	AS - Silver	20
BAS600AS270	AS - Silver	20
BAS800AS270	AS - Silver	10
BAS400AT270	AT - Titanium	20
BAS600AT270	AT - Titanium	20

Article	Finish	pcs/pck
BAS400AOSB270	AOSB - Brushed bright gold	20
BAS600AOSB270	AOSB - Brushed bright gold	20

Article	Finish	pcs/pck
BAC400AS	AS - Silver	1
BAC600AS	AS - Silver	1
BAC800AS	AS - Silver	1
BAC400AT	AT - Titanium	1
BAC600AT	AT - Titanium	1

Article	Finish	pcs/pck
BAC400AOSB	AOSB - Brushed bright gold	1
BAC600AOSB	AOSB - Brushed bright gold	1

Article	Finish	pcs/pck
BAS400AM11270	AM11 - Mat white	20
BAS600AM11270	AM11 - Mat white	20
BAS800AM11270	AM11 - Mat white	10
BAS400A54270	A54 - Mat black	20
BAS600A54270	A54 - Mat black	20
BAS800A54270	A54 - Mat black	10

Article	Finish	pcs/pck
BAC400AM11	AM11 - Mat white	1
BAC600AM11	AM11 - Mat white	1
BAC800AM11	AM11 - Mat white	1
BAC400A54	A54 - Mat black	1
BAC600A54	A54 - Mat black	1
BAC800A54	A54 - Mat black	1

APPLICATION

1. Cut the baseboard to the desired length.
2. Clean the wall support from residual oil, grease and dirt in general.
3. Apply FIXXTEC multipurpose sealant inside the grooves in the back (in case of profile with adhesive, remove the protective film).
4. Press the profile against the wall by exerting proper pressure.
5. Use the accessories for a workmanlike installation.

CLEANING AND MAINTENANCE

Do not use abrasive cleaners for cleaning. The profile requires no special care or maintenance.

Profilitec S.p.A.
Via Scotte, 3 - 36033 Isola Vicentina (Vicenza), ITALY
Tel: +39 0444 268311
e-mail: profilitec@profilitec.com

Profilitec Corp.
e-mail: customerservice@profilitec.com

Profilitec Ibérica, S.L.U.
e-mail: iberica@profilitec.com

